
:	HZZFCG	i-2023-109
0		
1	ISO9001 ISO14001 ISO45001	0-2 0.0 2.0 2.0 0.0 2.0
2	1 1 2 2 @ 0.5 2.5	0-3.5 0.0 3.5 3.5 0.0 3.5
3	1 3 0.5 ŏ ñ! 0.25 0.5 4	0.8 0.0 4.0 4.0 4.0 0.0 4.0
4	2000006 1 0.5 3 A A	0-3 0.0 3.0 3.0 0.0 3.0
5	() - 1 -	0-1 0.0 1.0 1.0 0.0 1.0
6	5 ""	

7	2. ≤0.1mg/L GB18584-2001 GB/T3324-2017 GB/T10357.2-2013 5 3. QB/T 2741-2013 GB 8624 B1 GB20286- 2006 1 QB/T4371 99% 1 1 3	0-3	0.0	1.0	3.0	3.0	0.0	2.0
8	CNAS CMA 1 GB20286- 2006 1 GB8624-2012 B1 QB/T4371 99% 1 2 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01μg/m³, ≤0.01μg/m³, ≤0.01μg/m³ TVOC ≤0.01μg/m³ GB/T 15102-2017 GB/T 39600-2021 GB/T 35601-2017 GB/T17657-2013 GB 18584-2001 1 QB/T 2189-2013 10 0.5 4 GB/T18101-2013 GB18580-2017 HJ571-2010 , B1-B ≤0.08mg/m³ 0.5	0-3	0.0	0.09	3.0	3.0	0.0	3.0
9	1. 2. UV 3.							

	5 30 1 0.5	,						
	6. 1							
	0.5 3							
	3 0.5							
10.1	1.5 0.5	0-1.5	0.0	0.0	1.0	1.0	0.5	0.5
	12.5							
	1.							
	1mm 0.4mm, 2	,						
	0.5 2.							
	2 0.5 3.							
10.2		0- 12.5	5.0	5.5	7.0	8.0	6.0	7.5
10.2	2 0.5	12.5	3.0	0.0	7.0	0.0	0.0	7.5
	4.							
	0.5 5.							
	2 0.5 6.							
	1.5 0.5 7.							
	3							
	1 2. 1							
10.3	1 3.	0-3	1.0	1.0	2.0	2.0	1.0	2.0
	≥3mm 1 1							
	3							
	1. (1) 1							
10.4	0.5 (2)	0-3	1.0	1.0	2.0	2.0	1.0	2.0
	1 0.5 2.							
	1 0.5							
11		0-3	1.0	1.0	1.0	1.0	1.0	1.0
 	3/50	 	l	l 	l 	I	l 	

	1		3								
12				1	0-1	1.0	1.0	1.0	1.0	1.0	1.0
13.1	:	""		1 ,	0-2	1.0	1.0	1.0	1.0	1.0	2.0
13.2	0.5	0.5			0-0.5	0.0	0.5	0.5	0.5	0.5	0.5
14		3		2	0-2	0.0	2.0	2.0	2.0	0.0	2.0
					0-60	10.0	27.5	46.0	46.5	12.0	45.0



•	HZZFOG-2023-109					
1	ISO9001 ISO14001 ISO45001	0-2	2.0	2.0	2.0	2.0
2	1 2 0.5 2.5	0-3.5	3.5	2.5	3.5	3.5
3	1 3 0.5 1 0.25 0.5 4	0-4	4.0	0.0	4.0	4.0
4	2020 6 1 0.5 3 A	0-3	3.0	1.0	3.0	3.0
5	- (- (1	0-				

8	CNAS CMA 1 GB20286-2006 1 GB8624-2012 B1 QB/T4371 99% 1 2 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01μg/m³, ≤0.01μg/m³, ≤0.01μg/m³ GB/T 15102-2017 GB/T 39600-2021 GB/T 35601-2017 GB/T17657-2013 GB 18584-2001 1 3 QB/T 2189-2013 10 0.5 4 GB/T18101-2013 GB18580-2017 HJ571-2010 B1-B ≤0.08mg/m³ 0.5	0-3	3.0	0.5	3.0	3.0
9	1. 2. UV 3. 4. 5. voc 30 1 0.5 , 30 5 6. 1 3 0.5 3 0.5	0-7	6.0	0.0	5.0	5.5
10.1	1.5 0.5	0-1.5	1.5	0.0	1.0	1.0
	12.5 1. 1mm 0.4mm, 0.5 2. 2 0.5 3.					

10.2	2 0.5 4. 2 0.5 5. 2 0.5 6. 0.5 7. 0.5	0- 12.5	11.0	5.5	9.0	8.5
10.3	3 1. 1 1 2. 1 1 3. ≥3mm 1	0-3	2.0	1.0	2.0	2.0
10.4	1. (1) 1 0.5 (2) 1 0.5 2. 1 0.5	0-3	2.5	2.0	2.0	2.0
11	1	0-3	1.0	1.0	1.0	1.0
12	1	0-1	1.0	1.0	1.0	1.0
13.1	" " : 2 1	0-2	2.0	1.0	2.0	1.0
13.2	0.5	0-0.5	0.5	0.0	0.5	0.5
14	3 2	0-2	2.0	0.0	0.0	0.0
		0-60	54.0	19.5	46.0	45.0

		1						
1	ISO9001 ISO14001 ISO45001	0-2	0.0	2.0	2.0	2.0	0.0	2.0
2	1 1 2 0.5 2.5	0-3.5	0.0	3.5	3.5	3.5	0.0	3.5
3	0.5 1 0.25 0.5 4	0-4	0.0	4.0	4.0	4.0	0.0	4.0
4	2020 6 1 0.5 3 A A	0-3	0.0	3.0	3.0	3.0	0.0	3.0
5	() 1	0-1	0.0	1.0	1.0	1.0	0.0	1.0
6	5 " " 1 0.5	0-5	0.0	0.0	4.0	3.0	0.0	3.0
	CNAS CMA 1. QB/T2741-2023 GB/T35607-2017 ≥40 W3≥350 W4≥50 ≤9% 100H ≤0.013mg/m3 TVOC							
ı	8/50	1	• !	•	·	•		, 1

Î		≤0.07mg/m3 200N 500N							
	7	2.	0-3	0.0	1.0	3.0	3.0	0.0	2.0
		≤0.1mg/L GB18584-2001 GB/T3324-2017 GB/T10357.2-2013 5							
		3. QB/T 2741-2013 GB 8624 B1 GB20286- 2006 1 QB/T4371 99% 1							
-		CNAS CMA							
	8	1 GB20286- 2006 1 GB8624-2012 B1 QB/T4371 99% 1 2 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01µg/m³, ≤0.01µg/m³, ≤0.01µg/m³ TVOC ≤0.01µg/m³ GB/T 15102-2017 GB/T 39600-2021 GB/T 35601-2017 GB/T17657-2013 GB 18584-2001 1 QB/T 2189-2013 4 GB/T18101-2013 GB18580-2017 HJ571-2010 , B1-B ≤0.08mg/m³ 0.5	0-3	0.0	0.0	3.0	3.0	0.0	3.0
		1. 2. UV 3.							
		4. 5. voc							
	9		0-7	0.0	0.0	5.0	5.5	0.0	5.0
		9/50							

	() 30 5 30 1 0.5 ,							
	6. 1							
	0.5 3 3 0.5							
10.1	1.5 0.5	0-1.5	0.0	0.0	1.0	1.0	0.5	0.5
	12.5 1. 1mm 0.4mm, 2 0.5 2. 2 0.5 3.							
10.2	2 0.5 4. 2 0.5 5. 2 0.5 6. 1.5 0.5 7. 0.5	0- 12.5	5.0	9.0	12.0	12.0	8.0	8.0
10.3	3 1. 1 2. 1 3. ≥3mm 1 1	0-3	1.0	1.0	3.0	3.0	1.0	1.0
10.4	3 1. (1)	0-3	1.0	1.5	3.0	3.0	1.5	1.5
	10/50							

11							0-3	1.0	1.0	3.0	3.0	1.0	1.0
		1			3								
12						1	0-1	0.0	0.0	1.0	1.0	0.0	0.0
13.1		:	es :	2		1 ,	0-2	1.0	1.0	2.0	2.0	1.0	1.0
13.2		0.5	0.5				0-0.5	0.0	0.5	0.5	0.5	0.5	0.5
14				3		2	0-2	0.0	2.0	2.0	2.0	0.0	2.0
	•	•					0-60	9.0	30.5	56.0	55.5	13.5	42.0

1	ISO9001 ISO14001 ISO45001	0-2	2.0	2.0	2.0	2.0
2	1 2 0.5 2.5	0-3.5	3.5	2.5	3.5	3.5
3	1 3 0.25 0.5 4 0.5	0-4	4.0	0.0	4.0	4.0
4	2020 6 1 0.5 3 A	0-3	3.0	1.0	3.0	3.0
5	- (- (1	0-1	1.0	1.0	1.0	1.0
6	1 0.5	0-5	5.0	1.0	3.0	3.0
7	CNAS CMA 1. QB/T2741- 2023 GB/T35607-2017 ≥40 W3≥350 W4≥50 ≤9% 100H ≤0.013mg/m3 TVOC ≤0.07mg/m3 200N 500N 2. ≤0.1mg/L GB18584-2001 GB/T3324- 2017 GB/T10357.2-2013 5 3. QB/T 2741-2013 GB 8624 B1 GB20286-2006 1 QB/T4371 99% 1 1 3		3.0	0.0	3.0	3.0

8	CNAS CMA 1 GB8624-2012 B1 QB/T4371 99% 1 2 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01μg/m³, ≤0.01μg/m³,	0-3	3.0	0.5	3.0	3.0
9	1. 2. UV 3. 4. 5. voc 30 1 0.5 , . 6. 1 3 0.5 3 0.5	0-7	6.0	0.0	5.0	5.5
10.1	1.5 0.5	0-1.5	1.5	0.0	1.0	1.0
	12.5 1. 1mm 0.4mm, 0.5 2. 2 0.5 3.					

10.2	2 0.5 4. 2 0.5	0- 12.5	10.0	5.0	9.0	12.0
	5. 2 6. 0.5 7. 1 0.5					
10.3	3 1. 1 1 2. 1 1 3. ≥3mm 1	0-3	2.0	1.0	2.0	3.0
10.4	3 1. (1) 1 0.5 (2) 1 0.5 2. 1 0.5	0-3	2.0	1.0	2.0	3.0
11	3	0-3	3.0	1.0	1.0	3.0
12	1	0-1	1.0	0.0	1.0	1.0
13.1	" " : 2 1	0-2	1.0	1.0	1.0	2.0
13.2	0.5	0-0.5	0.5	0.0	0.5	0.5
14	3 2	0-2	2.0	0.0	0.0	0.0
		0-60	53.5	17.0	45.0	53.5

1					

7 2. GB18584-2001 GB/T3324-2017 GB/T10357-2-2013 3. QB/T 2741-2013 GB 8824 B1 GB20286-2006 1 QB/T4371 99% 1 1 3 CNAS CMA 1 GB20286-2006 1 GB/824-2012 B1 QB/T4371 99% 20.80Mpa 24h 22.5% 20.80Mpa 2180Mpa 21550N 2120N 50.07µg/m², S0.01µg/m² S0.01µg/m² GB/T 15102-2017 GB/T 39600-2021 GB/T 35601-2017 GB/T 39600-2021 GB/T 3601-2017 GB/T 39600-2021 GB/T 3601-2017 GB/T 39600-2021 GB/T 3601-2013 GB/T 15102-2013 GB/T 15000-2011 GB/T 3601-2013 GB/T 15102-2013 GB/T 15102-2013 GB/T 15000-2011 GB/T 3601-2013 GB/T 15102-2013 GB/T 15102-2013 GB/T 15000-2011 GB/T 3601-2013 GB/T 15102-2013 GB/T 15000-2011 GB/T 3600-2013 GB/T 15102-2013 GB/T 15000-2013 GB/T 150		≤0.07mg/m3 200N 500N							
GB15864-2011 GB/T3324-2017 GB/T10375-2-2013 3	7		0-3	0.0	1.0	3.0	3.0	0.0	2.0
GB 8624 B1 GB20286- 2006 1 GB74371 1 3 CNAS CMA 1 GB80286- 2006 1 GB8024-2012 B1 QB/T4371 99% 2 ≥18 ≥2.5% ≥0.80Mpa ≥1.80Mpa ≥3400Mpa 24h ≥2.5% ≥0.80Mpa ≥1.80Mpa ≥0.02mg/m²(≥50h) ≤0.01µg/m² GB/T 15102-2017 GB7 35800-2021 GB/T 35601-2017 GB7 35800-2017 GB/T 35800-2017 GB7 35800-2017 GB/T 35601-2017 GB7 35800-2017 GB/T 35800-2017 GB7 358		GB18584-2001 GB/T3324-2017 GB/T10357.2-2013							
1 GB20286- 2006 1 GB8624-2012 B 99% 2 ≥18		GB 8624 B1 GB20286- 2006 1 QB/T4371 99% 1							
1 GB8624-2012 B1 QB/T4371 99% 1 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥180Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01µg/m³, ≤0.01µg/m³, ≤0.01µg/m³ TVOC ≤0.01µg/m³ GB/T 15102-2017 GBR 73000-2021 GB/T 35601-2017 GBR 717657-2013 GB 18584-2001 3 QB/T 2189-2013 10 0.5 4 GB/T18101-2013 GB18580-2017 HJ571-2010 B1-B ≤0.08mg/m³ 0.5 1. 2. UV 3. 4. 5. voc		CNAS CMA							
2. UV 3. 4. 5. voc 9 0-7 0.0 0.0 5.0 5.5 0.0 5.0	8	2006 1 GB8624-2012 B1 QB/T4371 99% 1 2 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01μg/m³, ≤0.01μg/m³, ≤0.01μg/m³ TVOC ≤0.01μg/m³ GB/T 15102-2017 GB/T 39600-2021 GB/T 35601-2017 GB/T17657-2013 GB 18584-2001 1 3 QB/T 2189-2013 10 0.5 4 GB/T18101-2013 GB18580-2017 HJ571-2010 , B1-B	0-3	0.0	0.0	3.0	3.0	0.0	3.0
4. 5. voc 0-7 0.0 0.0 5.0 5.5 0.0 5.0									
9 5. voc 0-7 0.0 0.0 5.0 5.5 0.0 5.0		3.							
9 0-7 0.0 0.0 5.0 5.5 0.0 5.0		4.							
		5. voc							
16/50	9		0-7	0.0	0.0	5.0	5.5	0.0	5.0
I O/ JO		16/50							

	() 30 5 30 1 0.5 ,							
	6. 1 3 0.5 3							
	3 0.5							
10.1	1.5 0.5	-1.5	0.0	0.0	1.0	1.0	0.5	0.5
	12.5							
	1mm 0.4mm, 2							
	0.5 2. 2 0.5							
	3.	0-						
10.2	2 0.5	0- 2.5	6.5	6.5	11.0	10.0	8.0	10.0
	4. 2							
	0.5 5. 2 0.5							
	6. 1.5 0.5 7. 1							
	1. 1							
10.3		0-3	1.0	1.0	3.0	3.0	1.0	3.0
	3. ≥3mm 1 1							
	3 1. (1)							
10.4	0.5		, _	10	0.0	0.0		0.0
10.4	1 0.5	0-3	1.5	1.0	2.0	2.0	1.0	2.0
	1 0.5							
	17/50	<u> </u>	ļ				1	l

11						0-3	1.0	1.0	1.0	3.0	1.0	1.0
	1			3								
12					1	0-1	1.0	1.0	1.0	1.0	1.0	1.0
13.1	:	и з	2		1 ,	0-2	1.0	1.0	2.0	2.0	1.0	1.0
13.2	0.5	0.5				0-0.5	0.0	0.5	0.5	0.5	0.5	0.5
14			3		2	0-2	0.0	2.0	2.0	2.0	0.0	2.0
						0-60	12.0	28.5	52.0	52.5	14.0	47.5

1	ISO9001 ISO14001 ISO45001	0-2	2.0	2.0	2.0	2.0
2	1 1 2 0.5 2.5	0-3.5	3.5	2.5	3.5	3.5
3	1 3 0.5 1 0.25 0.5 4	0-4	4.0	0.0	4.0	4.0
4	2020 6 1 0.5 3 A	0-3	3.0	1.0	3.0	3.0
5	- (- (1	0-1	1.0	1.0	1.0	1.0
6	1 0.5	0-5	5.0	1.0	3.0	3.0
7	CNAS CMA 1. QB/T2741- 2023 GB/T35607-2017 ≥40 W3≥350 W4≥50 ≤9% 100H ≤0.013mg/m3 TVOC ≤0.07mg/m3 200N 500N 2. ≤0.1mg/L GB18584-2001 GB/T3324- 2017 GB/T10357.2-2013 5 3. QB/T 2741-2013 GB 8624 B1 GB20286-2006 1 QB/T4371 99% 1 1 3	0-3	3.0	0.0	3.0	3.0

8	CNAS CMA 1 GB20286-2006 1 GB8624-2012 B1 QB/T4371 99% 1 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01μg/m³, ≤0.01μg/m³,	0-3	3.0	0.5	3.0	3.0
9	1. 2. UV 3. 4. 5. voc 30 1 0.5 , 30 5 6. 1 3 0.5 3 0.5	0-7	6.0	0.0	5.0	5.5
10.1	1.5 0.5	0-1.5	1.5	0.0	1.0	1.0
	12.5 1. 1mm 0.4mm, 2 0.5 2. 2 0.5 3.					

10.2	2 0.5 4. 2 0.5	0- 12.5	11.5	6.0	10.0	11.0
	5. 2 0.5 6. 1.5 7. 0.5					
10.3	3 1. 1 1 2. 1 1 3. ≥3mm 1	0-3	3.0	1.0	3.0	3.0
10.4	3 1. (1) 1 0.5 (2) 1 0.5 2. 1 0.5	0-3	2.5	1.0	2.0	2.5
11	3	0-3	3.0	1.0	3.0	3.0
12	1	0-1	1.0	1.0	1.0	1.0
13.1	" " : 2 1	0-2	2.0	1.0	2.0	2.0
13.2	0.5	0-0.5	0.5	0.0	0.5	0.5
14	3 2	0-2	2.0	0.0	0.0	0.0
		0-60	57.5	19.0	50.0	52.0

•	HZZFGG-	_0_0			
1					

		≤0.07mg/m3 200N 500N							
	7	2.	0-3	0.0	1.0	3.0	3.0	0.0	2.0
		≤0.1mg/L GB18584-2001 GB/T3324-2017 GB/T10357.2-2013 5 3. QB/T 2741-2013 GB 8624 B1 GB20286- 2006 1 QB/T4371 99% 1 1 3							
	8	CNAS CMA 1 GB20286- 2006 1 GB8624-2012 B1 QB/T4371 99% 1 2 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01μg/m³, ≤0.01μg/m³, ≤0.01μg/m³ TVOC ≤0.01μg/m³ GB/T 15102-2017 GB/T 39600-2021 GB/T 35601-2017 GB/T17657-2013 GB 18584-2001 1 3 QB/T 2189-2013 10 0.5 4 GB/T18101-2013 GB18580-2017 HJ571-2010 , B1-B ≤0.08mg/m³ 0.5	0-3	0.0	0.0	3.0	3.0	0.0	3.0
	9	1. 2. UV 3. 4. 5. voc	0-7	0.0	0.0	5.0	5.5	0.0	5.0
		23/50		l .	·				ı I

	() 30 5 30 1 0.5 ,							
	6. 1							
	0.5 3 3 0.5							
10.1	1.5 0.5	0-1.5	0.0	0.0	1.0	0.5	0.5	0.5
10.2	12.5 1. 1mm 0.4mm, 2 0.5 2. 2 0.5 3.	0- 12.5	6.0	6.5	12.0	10.0	6.5	9.0
	2 0.5 4. 2 0.5 5. 2 0.5 6. 1.5 0.5 7. 0.5							
10.3	3 1.	0-3	1.0	1.0	3.0	2.0	1.0	2.0
10.4	3 1. (1)	0-3	1.0	0.5	3.0	2.0	0.5	2.0
	24/50							

11			0-3	1.0	1.0	3.0	1.0	1.0	3.0
		3							
12		1	0-1	0.0	1.0	1.0	1.0	1.0	1.0
13.1		: 2 1	0-2	0.0	1.0	2.0	1.0	1.0	2.0
13.2		0.26 1 2 O v 0 Z							
	I								

1	ISO9001 ISO14001 ISO45001	0-2	2.0	2.0	2.0	2.0
2	1 2 0.5 2.5	0-3.5	3.5	2.5	3.5	3.5
3	1 3 0.25 0.5 1 0.25 4	0-4	4.0	0.0	4.0	4.0
4	2020 6 1 0.5 3 A	0-3	3.0	1.0	3.0	3.0
5	- (- (1	0-1	1.0	1.0	1.0	1.0
6	1 0.5	0-5	5.0	1.0	3.0	3.0
7	CNAS CMA 1. QB/T2741- 2023 GB/T35607-2017 ≥40 W3≥350 W4≥50 ≤9% 100H ≤0.013mg/m3 TVOC ≤0.07mg/m3 200N 500N 2. ≤0.1mg/L GB18584-2001 GB/T3324- 2017 GB/T10357.2-2013 5 3. QB/T 2741-2013 GB 8624 B1 GB20286-2006 1 QB/T4371 99% 1 1 3	0-3	3.0	0.0	3.0	3.0

8	CNAS CMA 1 GB8624-2012 B1 QB/T4371 99% 1 2 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01µg/m³, ≤0.01µg/m³,	0-3	3.0	0.5	3.0	3.0
9	1. 2. UV 3. 4. 5. voc 30 1 0.5 , . 6. 1 3 0.5 3 0.5	0-7	6.0	0.0	5.0	5.5
10.1	1.5 0.5	0-1.5	1.5	0.0	1.0	1.0
	12.5 1. 1mm 0.4mm, 2 0.5 2. 2 0.5 3.					

10.2	2 0.5 4. 2 0.5 5. 2 6. 0.5 7. 0.5	0- 12.5	9.0	6.0	8.0	9.0
10.3	3 1. 1 1 2. 1 1 3. ≥3mm 1	0-3	2.0	1.0	1.0	1.0
10.4	3 1. (1) 1 0.5 (2) 1 0.5 2. 1 0.5	0-3	1.0	0.5	1.0	1.0
11	3	0-3	3.0	0.0	1.0	1.0
12	1	0-1	1.0	0.0	1.0	1.0
13.1	" " : 2 1	0-2	1.0	0.0	1.0	1.0
13.2	0.5	0-0.5	0.5	0.0	0.5	0.5
14	3 2	0-2	2.0	0.0	0.0	0.0
		0-60	51.5	15.5	42.0	43.5

1	ISO9001 ISO14001 ISO45001	0-2	0.0	2.0	2.0	2.0	0.0	2.0
2	1 1 2 1 2 0.5	0-3.5	0.0	3.5	3.5	3.5	0.0	3.5
3	0.5 1 3 0.5 1 0.25 0.5 4	0-4	0.0	4.0	4.0	4.0	0.0	4.0
4	2020 6 1 0.5 3 A A	0-3	0.0	3.0	3.0	3.0	0.0	3.0
5	() ()- 1	0-1	0.0	1.0	1.0	1.0	0.0	1.0
6	5 " " 1 0.5	0-5	0.0	0.0	4.0	3.0	0.0	3.0
	CNAS CMA 1. QB/T2741-2023 GB/T35607-2017 ≥40 W3≥350 W4≥50 ≤9% 100H ≤0.013mg/m3 TVOC							

	≤0.07mg/m3 200N 500N			Ī					
7	2.)-3	0.0	1.0	3.0	3.0	0.0	2.0	
	≤0.1mg/L GB18584-2001 GB/T3324-2017 GB/T10357.2-2013 5								
	3. QB/T 2741-2013 GB 8624 B1 GB20286- 2006 1 QB/T4371 99% 1								
	CNAS CMA								
	1 GB20286- 2006 1 GB8624-2012 B1 QB/T4371 99% 1 ≥18								
8	Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01μg/m³, ≤0.01μg/m³, 0 ≤0.01μg/m³ TVOC ≤0.01μg/m³ GB/T 15102-2017 GB/T 39600-2021 GB/T 35601-2017)-3	0.0	0.0	3.0	3.0	0.0	3.0	
	GB/T17657-2013 GB 18584-2001 1 3 QB/T 2189-2013 10 0.5 4 GB/T18101-2013 GB18580-2017 HJ571-2010								
	, B1-B ≤0.08mg/m³ 0.5								
	1.								
	2. UV								
	3.								
	4.								
9	5. voc)-7	0.0	0.0	5.0	5.5	0.0	5.0	
	30/50								

	() 30 5 30 1 0.5 ,						
	6. 1 3 0.5 3						
	3 0.5						
10.1	1.5 0.5 0-1.9	5 0.0	0.0	1.0	1.0	0.5	0.5
	12.5						
	1mm 0.4mm, 2						
	0.5 2. 2 0.5						
	3.						
10.2	0- 12.5	6.0	6.0	10.0	12.0	4.0	8.0
	2 0.5 4.						
	0.5						
	5. 2 0.5 6. 1.5 0.5						
	7.						
	1. 1 1						
10.3	2. 1 3. 0-3	1.0	1.0	2.0	3.0	1.0	2.0
	≥3mm 1 1						
	3 1. (1)						
10.4	0.5 (2)	1.0	1.0	2.0	3.0	1.0	2.0
10.4	1 0.5 2.	1.0	1.0	2.0	3.0	1.0	2.0
	1 0.5						
	31/50			<u></u> _			

11						0-3	1.0	1.0	1.0	3.0	1.0	1.0
	1			3								
12					1	0-1	1.0	1.0	1.0	1.0	1.0	1.0
13.1	:	и ,	2		1 ,	0-2	1.0	1.0	2.0	2.0	1.0	2.0
13.2	0.5	0.5				0-0.5	0.0	0.5	0.5	0.5	0.5	0.5
14			3		2	0-2	0.0	2.0	2.0	2.0	0.0	2.0
						0-60	11.0	28.0	50.0	55.5	10.0	45.5

†						
1	ISO9001 ISO14001 ISO45001	0-2	2.0	2.0	2.0	2.0
2	1 2 0.5 2.5	0-3.5	3.5	2.5	3.5	3.5
3	1 3 0.5 1 0.25 0.5 4	0-4	4.0	0.0	4.0	4.0
4	2020 6 1 0.5 3 A	0-3	3.0	1.0	3.0	3.0
5	- () - (1	0-1	1.0	1.0	1.0	1.0
6	1 0.5	0-5	5.0	1.0	3.0	3.0
	CNAS CMA 1. QB/T2741- 2023 GB/T35607-2017 ≥40 W3≥350 W4≥50 ≤9% 100H ≤0.013mg/m3 TVOC ≤0.07mg/m3 200N 500N 2. ≤0.1mg/L GB18584-2001 GB/T3324- 2017 GB/T10357.2-2013 5 3. QB/T 2741-2013 GB 8624 B1 GB20286-2006 1 QB/T4371 99% 1 1 3	0-3	3.0	0.0	3.0	3.0

8	CNAS CMA 1 GB20286-2006 1 GB8624-2012 B1 QB/T4371 99% 1 2 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01μg/m³, ≤0.01μg/m³,	0-3	3.0	0.5	3.0	3.0
9	1. 2. UV 3. 4. 5. voc 30 1 0.5 , . 6. 1 3 0.5 3 0.5	0-7	6.0	0.0	5.0	5.5
10.1	1.5 0.5	0-1.5	1.5	0.0	1.0	1.0
	12.5 1. 1mm 0.4mm, 2 0.5 2. 2 0.5 3.					

10.2	2 0.5 4. 2 0.5 5. 2 0.5 6. 0.5 7. 0.5	0- 12.5	8.0	6.0	6.0	8.0
10.3	3 1. 1 1 2. 1 1 3. ≥3mm 1	0-3	2.0	1.0	2.0	1.0
10.4	3 1. (1) 1 0.5 (2) 1 0.5 2. 1 0.5	0-3	2.0	1.0	2.0	2.0
11	3	0-3	1.0	1.0	1.0	1.0
12	1	0-1	1.0	1.0	1.0	1.0
13.1	" " : 2 1	0-2	2.0	1.0	2.0	1.0
13.2	0.5	0-0.5	0.5	0.0	0.5	0.5
14	3 2	0-2	2.0	0.0	0.0	0.0
		0-60	50.5	19.0	43.0	43.5

:

1	ISO9001 ISO14001 ISO45001	0-2	0.0	2.0	2.0	2.0	0.0	2.0
2	1 1 2 0.5 2.5	0-3.5	0.0	3.5	3.5	3.5	0.0	3.5
3	0.5 1 0.25 0.5 4	0-4	0.0	4.0	4.0	4.0	0.0	4.0
4	2020 6 1 0.5 3 A	0-3	0.0	3.0	3.0	3.0	0.0	3.0
5	() - ()- 1	0-1	0.0	1.0	1.0	1.0	0.0	1.0
6	5 "" 1 0.5	0-5	0.0	0.0	4.0	3.0	0.0	3.0
	CNAS CMA							

		≤0.07mg/m3 200N 500N							
	7	2.	0-3	0.0	1.0	3.0	3.0	0.0	2.0
		≤0.1mg/L GB18584-2001 GB/T3324-2017 GB/T10357.2-2013 5 3. QB/T 2741-2013 GB 8624 B1 GB20286- 2006 1 QB/T4371 99% 1 1 3							
	8	CNAS CMA 1 GB20286- 2006 1 GB8624-2012 B1 QB/T4371 99% 1 2 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01μg/m³, ≤0.01μg/m³, ≤0.01μg/m³ TVOC ≤0.01μg/m³ GB/T 15102-2017 GB/T 39600-2021 GB/T 35601-2017 GB/T17657-2013 GB 18584-2001 1 3 QB/T 2189-2013 10 0.5 4 GB/T18101-2013 GB18580-2017 HJ571-2010 , B1-B ≤0.08mg/m³ 0.5	0-3	0.0	0.0	3.0	3.0	0.0	3.0
	9	1. 2. UV 3. 4. 5. voc	0-7	0.0	0.0	5.0	5.5	0.0	5.0
I		37/50		I .					· '

10.1		() 30 5 30 1 0.5 ,							
10.1 1.5 1.5 0.5 0.1.5 0.0 0.0 1.0 1.0 0.5 0.5 10.2 1. 1. 1. 1. 1. 1. 1.		0.5 3							
10.2 1. 12.5 1. 1. 1. 2. 0.5 1. 0.3 0.0 0.0 3.0 2.0 0.0 2.0 1.0 2.0 2.0 1.0 2.0 2.0 1.0 2.0		0.5							
1. 1mm 0.4mm, 2 0.5 2. 2 0.5 3.0 4.0 11.0 9.0 4.0 9.0 10.2 2 0.5 3.	10.1	1.5 0.5	0-1.5	0.0	0.0	1.0	1.0	0.5	0.5
10.2 0.5 2 0.5 3.0 4.0 11.0 9.0 4.0		12.5							
10.2 2		2 0.5							
2 0.5 4. 2 0.5 5. 2 0.5 6. 7. 0.5 1 10.3 1. 1. 2. 1. 3. 1. 2. 3. 1. 1. 1. 1. 2. 1. 3. 23mm 1 1 1 1 0-3 0.0 0.0 0.0 3.0 2.0 0.0 2.0 1.0 2.0 2.0 1.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2.0 2		2. 2 0.5 3.							
4. 2	10.2		0- 12.5	3.0	4.0	11.0	9.0	4.0	9.0
5. 2 0.5 6. 1.5 7. 0.5 1		4.							
10.3		5. 2 0.5 6. 1.5 0.5							
10.3		0.5							
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	10.3	1. 1 2. 1 3.	0-3	0.0	0.0	3.0	2.0	0.0	2.0
10.4 1.		≥3mm 1 1							
10.4 (2) 1 0.5 1 0.5 1 0.5		1. (1)							
1 0.5	10.4	1 0.5	0-3	0.0	1.0	2.0	2.0	1.0	2.0
00/50									

11					Ī	0-3	1.0	1.0	3.0	1.0	0.0	3.0
	1			3								
12					1	0-1	0.0	1.0	1.0	1.0	0.0	1.0
13.1	:	и ,	2		1 ,	0-2	2.0	0.0	2.0	1.0	1.0	1.0
13.2	0.5	0.5				0-0.5	0.0	0.5	0.5	0.5	0.5	0.5
14			3		2	0-2	0.0	2.0	2.0	2.0	0.0	2.0
						0-60	6.0	24.0	54.0	47.5	7.0	47.5

HZZFCG-2023-109

1	ISO9001 ISO14001 ISO45001	0-2	2.0	2.0	2.0	2.0
2	1 1 2 0.5 2.5	0-3.5	3.5	2.5	3.5	3.5
3	1 3 0.5 1 0.25 0.5 4	0-4	4.0	0.0	4.0	4.0
4	2020 6 1 0.5 3 A A	0-3	3.0	1.0	3.0	3.0
5	- (- (1	0-1	1.0	1.0	1.0	1.0
6	1 0.5	0-5	5.0	1.0	3.0	3.0
7	CNAS CMA 1. QB/T2741- 2023 GB/T35607-2017 ≥40	0-3	3.0	0.0	3.0	3.0
I	40/50	ı l	Į.	1	ļ	ļ

40/50

8	CNAS CMA 1 GB20286-2006 1 GB8624-2012 B1 QB/T4371 99% 1 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N ≥1200N ≤0.02mg/m³(≥50h) ≤0.01µg/m³, ≤0.01µg/m³,		3.0	0.5	3.0	3.0
9	1. 2. UV 3. 4. 5. voc 30 1 0.5 , . 6. 1 3 0.5 3 0.5	0-7	6.0	0.0	5.0	5.5
10.1	1.5 0.5	0-1.5	1.5	0.0	1.0	1.0
	12.5 1. 1mm 0.4mm, 0.5 2. 2. 0.5 3.					

41/50

10.2	2 0.5 4. 2 0.5 5. 2 0.5 6. 0.5 7. 0.5	0- 12.5	12.0	3.0	8.0	9.0
10.3	3 1. 1 1 2. 1 1 3. ≥3mm 1	0-3	3.0	1.0	2.0	2.0
10.4	3 1. (1) 1 0.5 (2) 1 0.5 2. 1 0.5	0-3	3.0	1.0	2.0	2.0
11	3	0-3	3.0	0.0	1.0	3.0
12	1	0-1	1.0	0.0	1.0	1.0
13.1	" " : 2 1	0-2	2.0	1.0	1.0	1.0
13.2	0.5	0-0.5	0.5	0.0	0.5	0.5
14	3 2	0-2	2.0	0.0	0.0	0.0
		0-60	58.5	14.0	44.0	47.5

:

HZZFCG-2023-109

•	nzzrog-							
1	ISO9001 ISO14001 ISO45001	0-2	0.0	2.0	2.0	2.0	0.0	2.0
2	1 1 2 0.5 2.5	0-3.5	0.0	3.5	3.5	3.5	0.0	3.5
3	0.5 1 3 0.5 1 0.25 0.5 4	0-4	0.0	4.0	4.0	4.0	0.0	4.0
4	2020 6 1 0.5 3 A A	0-3	0.0	3.0	3.0	3.0	0.0	3.0
5	() 1	0-1	0.0	1.0	1.0	1.0	0.0	1.0
6	5 " " 1 0.5	0-5	0.0	0.0	4.0	3.0	0.0	3.0
	CNAS CMA 1. QB/T2741-2023 GB/T35607-2017 ≥40 W3≥350 W4≥50							

	≤0.07mg/m3 200N 500N								
7	2.	0-3	0.0	1.0	3.0	3.0	0.0	2.0	
	≤0.1mg/L GB18584-2001 GB/T3324-2017 GB/T10357.2-2013 5								
	3. QB/T 2741-2013 GB 8624 B1 GB20286- 2006 1 QB/T4371 99% 1								
	1 3								
	CNAS CMA								
	1 GB20286- 2006 1 GB8624-2012 B1 QB/T4371 99% 1 2 ≥18 Mpa ≥3400Mpa 24h ≤2.5% ≥0.80Mpa ≥1.80Mpa ≥1550N								
8	≥1200N ≤0.02mg/m³(0-3	0.0	0.0	3.0	3.0	0.0	3.0	
	0.5 4 GB/T18101-2013 GB18580-2017 HJ571-2010 , B1-B ≤0.08mg/m³ 0.5								
	1.								
	2. UV 3.								
	4.								
9	5. voc	0-7	0.0	0.0	5.0	5.5	0.0	5.0	
	44/50							·	

	() 30 5 30 1 0.5 ,							
	6. 1							
	0.5 3 3 0.5							
10.1	1.5 0.5	0-1.5	0.0	0.0	1.0	1.0	0.5	0.5
	12.5 1. 1mm 0.4mm, 2 0.5 2. 2 0.5 3.							
10.2	2 0.5 4. 2 0.5 5. 2 0.5 6. 1.5 0.5 7. 0.5	0- 12.5	5.0	6.0	8.0	11.0	6.0	11.0
10.3	3 1. 1 2. 1 3. ≥3mm 1 1	0-3	1.0	2.0	2.0	3.0	2.0	3.0
10.4	3 1. (1)	0-3	1.0	1.0	2.0	2.5	2.0	1.5
	45/50							

11						0-3	1.0	1.0	3.0	3.0	1.0	1.0
	1			3								
12					1	0-1	1.0	1.0	1.0	1.0	1.0	1.0
13.1	:	и ,	2		1 ,	0-2	1.0	2.0	2.0	2.0	1.0	2.0
13.2	0.5	0.5				0-0.5	0.0	0.5	0.5	0.5	0.5	0.5
14			3		2	0-2	0.0	2.0	2.0	2.0	0.0	2.0
						0-60	10.0	30.0	50.0	54.0	14.0	49.0

HZZFCG-2023-109

1	ISO9001 ISO14001 ISO45001	0-2	2.0	2.0	2.0	2.0
2	1 2 0.5 2.5	0-3.5	3.5	2.5	3.5	3.5
3	1 3 0.25 0.5 1 0.25 4	0-4	4.0	0.0	4.0	4.0
4	2020 6 1 0.5 3 A	0-3	3.0	1.0	3.0	3.0
5	- (- (1	0-1	1.0	1.0	1.0	1.0
6	1 0.5	0-5	5.0	1.0	3.0	3.0
7	CNAS CMA 1. QB/T2741- 2023 GB/T35607-2017 ≥40 W3≥350 W4≥50 ≤9% 100H ≤0.013mg/m3 TVOC ≤0.07mg/m3 200N 500N 2. ≤0.1mg/L GB18584-2001 GB/T3324- 2017 GB/T10357.2-2013 5 3. QB/T 2741-2013 GB 8624 B1 GB20286-2006 1 QB/T4371 99% 1 1 3	0-3	3.0	0.0	3.0	3.0

47/50

		Ca Dulak(dili akaid) NyuA <u>Pa</u> EseAiy @ yi yiA t				
	1 9Z	C PROPERTY DESCRIPTION OF THE PROPERTY OF THE		b ÿQ¥(fWs		
	1 亞漢河	ĬĸijŇŇ Ġ @& 《ŊŶijŊĠĸĠŷ fác ŊŊĠ ŷ%c <i>f</i> `f ×			NËË	
8						
			1			
			1			
			1			

10.2	2 0.5 4. 2 0.5 5. 2 0.5 6. 0.5 7. 0.5	0- 12.5	7.0	5.0	10.0	9.0
10.3	3 1. 1 1 2. 1 1 3. ≥3mm 1	0-3	2.0	2.0	2.0	3.0
10.4	3 1. (1) 1 0.5 (2) 1 0.5 2. 1 0.5	0-3	1.5	1.5	1.5	2.5
11	3	0-3	1.0	1.0	1.0	3.0
12	1	0-1	1.0	1.0	1.0	1.0
13.1	" " : 2 1	0-2	1.0	1.0	1.0	2.0
13.2	0.5	0-0.5	0.5	0.0	0.5	0.5
14	3 2	0-2	2.0	0.0	0.0	0.0
		0-60	48.0	19.5	45.5	50.0